

WHEELCHAIR LIFT ASSEMBLY HAVING A LIFT ARM SUPPORT

CROSS-REFERENCE TO RELATED APPLICATION

5 This application claims the benefit of U.S. Provisional Application No. 60/243,331, filed October 25, 2000, the disclosure of which is hereby expressly incorporated by reference.

FIELD OF THE INVENTION

10 The present invention relates generally to wheelchair lifts and, more particularly, to a support assembly for a lift arm of a motor vehicle wheelchair lift.

BACKGROUND OF THE INVENTION

15 The Americans with Disabilities Act (ADA) requires the removal of physical obstacles to those who are physically challenged. Included within the scope of the ADA are motor vehicles, such as trains and buses. Specifically, new, used or remanufactured buses shall comply with the applicable provisions of the statute. One such provision requires that deployed platforms, when occupied, shall prevent the platform from dropping an occupant in the event of a single failure of any load-carrying component. Thus, the ADA mandates that all load carrying components of a wheelchair lift cannot have single points of failure.

20 Currently, there are a wide variety of wheelchair lifts available for motor vehicles. One such lift is adapted to be reciprocally mounted within a luggage

compartment or stairwell of a bus or train. Such a lift includes a reciprocating platform mounted within the vehicle and a lift platform selectively actuatable between at least a raised and lowered position. The lift platform is hingedly attached to the reciprocating platform by two sets of hinge arm assemblies. The hinge arm assemblies are located on opposite sides of the lift platform and include a support arm and a balance arm. One end of the support and balance arms of each hinge arm assembly is pinned to opposite sides of the lift platform, while the other ends of the hinge arm assemblies are pinned to opposite sides of the reciprocating platform. As attached, the hinge arm assemblies reciprocate the lift platform between the raised position and the lowered position. Although such a lift is effective at accommodating wheelchair access into and out of a motor vehicle, it is not without its problems.

One of the major problems associated with currently available wheelchair lifts is the design of the hinge arm assemblies. Specifically, if one of the pins attaching the support arm to the lift platform fails, the lift platform would pivot about the pin attaching the balance arm to the lift platform, thereby potentially injuring a person located on the lift platform. This is due in part to the attachment location of the hinge arm assembly to the lift platform relative to the center of gravity of the lift platform.

Such a wheelchair lift is not only dangerous, it also fails to comply with the prohibition of the ADA regarding single point failure of any load carrying component. Further, such wheelchair lifts are also not in compliance with recent proposed revisions to the ADA establishing even more stringent requirements with at least regard to the single point of failure provision. Moreover, the proposed revisions to the ADA are also applicable to existing wheelchair lifts. Therefore, existing wheelchair lifts must be retrofitted.

For at least the foregoing reasons, there exists a need for a wheelchair lift that includes a redundant support in the event of a failure of a portion of the lift, wherein the redundant support complies with the ADA requirements, is economical to install and maintain, and may be easily retrofitted into existing wheelchair lifts.

SUMMARY OF THE INVENTION

In accordance with certain embodiments of the present invention, a wheelchair lift assembly is provided. The wheelchair lift assembly includes first and second attachment arm assemblies extending between a reciprocating platform and a lift platform. The lift platform is movable between at least a raised position and a lowered position. The lift platform is held in a substantially horizontal first plane as the lift platform is moved between at least the raised and lowered positions. The wheelchair lift assembly further includes a support device coupled to one of the first and second attachment arm assemblies, where the support device supports one of the first and attachment arm assemblies and maintains the lift platform in a second plane substantially parallel to the first plane if at least a portion of the other of the first and second attachment arm assembly fails.

In accordance with further aspects of this invention, the support device includes a bracket extending between an upper arm and a lower arm of one of either the first or second attachment arm assembly. In another aspect of this invention, the support device includes a second bracket extending between an upper arm and a lower arm of the other of the first or second attachment arm assembly.

In accordance with still yet another aspect of this invention, the support device includes a U-shaped first bracket pinned to one of an upper or lower arm of the first or second attachment arm assembly. In accordance with still yet another aspect of this invention, the support device includes a U-shaped bracket pinned to one of an upper or lower arm of each of the first and second attachment arm assemblies.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing aspects and many of the attendant advantages of this invention will become better understood by reference to the following detailed description, when taken in conjunction with the accompanying drawings, wherein:

FIGURE 1 is a perspective view of a wheelchair lift assembly having a support assembly formed in accordance with one embodiment of the present invention;

FIGURE 2 is a side planar view of a wheelchair lift having a support assembly formed in accordance with one embodiment of the present invention;

FIGURE 3 is a cross sectional view of the support assembly formed in accordance with one embodiment of the present invention taken substantially through

5 Section 3-3 of FIGURE 2;

FIGURE 4 is a partial perspective view of a wheelchair lift having a support assembly formed in accordance with another embodiment of the present invention;

FIGURE 5 is a cross sectional end view of the support assembly of FIGURE 4;

10 FIGURE 6 is a partial perspective view of a wheelchair lift having a support assembly formed in accordance with yet another embodiment of the present invention; and

FIGURE 7 is a cross-sectional view of the support assembly formed in accordance with the embodiment of FIGURE 6 and taken substantially through

15 Section 7-7 of FIGURE 6.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

20 FIGURES 1 and 2 illustrates one embodiment of a support assembly 20 formed in accordance with the present invention. The support assembly 20 is designed to be used with a wheelchair lift 22, such as the wheelchair lift disclosed in U.S. Patent No. 5,110,252, issued to Aoki, the disclosure of which is hereby expressly incorporated by reference. For clarity, the vehicle to which the wheelchair lift 22 can be installed has not been illustrated. Further, although the support assembly 20 is illustrated as fastened to a reciprocating platform lift, other types of wheelchair lifts, such as wheelchair lifts mounted in a stairwell of a vehicle, are also
25 within the scope of the present invention.

The wheelchair lift 22 includes a reciprocating platform 24, a pair of attachment arm assemblies 26a and 26b, and a lift platform 28. The reciprocating platform 24 is slidably attached to a pair of support rails (not shown) located within a vehicle (not shown). The support rails are in turn fastened to a support structure,

such as a passenger floor or stairwell, of the vehicle by well known fasteners, such as bolts.

5 The reciprocating platform 24 is adapted to slide within the support rails between a stowed position, wherein the wheelchair lift 22 is received within a stowage compartment located within the vehicle, and a deployed position, wherein the lift platform 28 is adapted to receive a wheelchair, as is described in greater detail below.

10 The attachment arm assemblies 26a and 26b are hingedly attached to one end of the reciprocating platform 24. As attached, the attachment arm assemblies are able to reciprocate the lift platform 28 between a lowered position, an intermediate position, and a raised position, as is well known in the art. In the lowered position, the lift platform 28 is located adjacent a curbside or loading platform. In this position, a wheelchair may be rolled on or off of the lift platform 28. In the intermediate position, the lift platform 28 is substantially level with the reciprocating platform 24, to permit withdrawal of the wheelchair lift 22 into the stowage compartment. Finally, in the raised position, the lift platform 28 is displaced upwardly to position the lift platform 28 adjacent an entryway of the motor vehicle.

15 Extending between the attachment arm assemblies 26a and 26b is a torsion tube 27. The torsion tube 27 is welded on each end to the attachment arm assemblies 26a and 26b. As well known in the art, the torsion tube 27 actuates the lift platform 28 between the lowered position, intermediate position and the raised position by applying torque to the attachment arm assemblies 26a and 26b.

20 Each attachment arm assembly 26a and 26b includes a support arm 30a and 30b and a balance arm 32a and 32b. Each attachment arm assembly 26a and 26b is identical. Therefore, for clarity, only one attachment arm assembly shall be described in greater detail. However, it should be apparent that the description for one attachment arm assembly is applicable to the other assembly.

25 One end of the support arm 30a and balance arm 32a is coupled to opposite sides of one end of the reciprocating platform 24 by a well known attachment pin assembly 40a and 40b, such as a trunnion or cantilevered pin. The other end of the

30

support arm 30a and balance arm 32a is similarly fastened to opposite sides of the lift platform 28 by a well known support arm pin 42 and balance arm pin 44. As coupled to both the reciprocating platform 24 and lift platform 28, the attachment arm assemblies 26a and 26b permit hinged movement of the lift platform 28 relative to the reciprocating platform 24.

Referring now to FIGURES 1 and 3, the support assembly 20 will now be described in greater detail. Although a single support assembly 20 is illustrated as attached to each one of the attachment arm assemblies 26a and 26b, the invention is not intended to be so limited. As a non limiting example, two or more support assemblies may be attached to each attachment arm assembly 26a and 26b. Further, each support assembly 20 is identical and, therefore, only one support assembly will be described in greater detail. However, it should be apparent that the description for one support assembly 20 is applicable to the other.

The support assembly 20 includes first and second plates 34a and 34b and a pair of support pins 36a and 36b. Each plate 34a and 34b is suitably a rectangular member formed from a high strength material, such as steel. The plates 34a and 34b are fastened to opposite sides of the support arm 30a and balance arm 32a by the strap pins 36a and 36b. As seen best by referring to FIGURE 3, the first strap pin 36a extends through one end of the first plate 34a, through a correspondingly located bore 46 extending laterally through the balance arm 32a, and through the second plate 34b. The second strap pin 36b extends through the first plate 34a, through a bore 48 extending laterally through the support arm 30a, and through the second plate 34b. Thus, as attached, the support arm 30a and balance arm 32a are sandwiched between the first and second plates 34a and 34b of the support assembly 20.

In operation, the lift platform 28 is supported by the support arms 30a and 30b. As noted above, the connection between the lift platform 28 and the support arms 30a and 30b is achieved by the support arm pin 42. The lift platform 28 is maintained in a substantially horizontal position throughout its range of motion by the connection between the balance arms 32a and 32b through the balance arm

pin 44. It should be apparent that the phrase "substantially horizontal position" includes the normal operating range of a wheelchair lift within the scope of this disclosure. Thus, such normal operating ranges are within the scope of all embodiments of the present invention.

5 In the event of a failure of one of the balance arm pins 44, the lift platform 28 is maintained level by the balance arm located on the opposite side of the lift platform 28. Although the lift platform 28 may drop slightly from its originally supported position, the support assembly 20 maintains the lift platform 28 in a plane substantially parallel to its original horizontal plane. As an example, in the event of
10 failure of the balance arm pin 44 connecting the balance arm 32a to the lift platform 28, the other balance arm 32b maintains the level positioning of the lift platform 28.

In the event of a failure of one of the support arm pins 42, the lift platform load is transferred to the balance arms 32a and 32b by the support assembly 20. The
15 first and second plates 34a and 34b of each support assembly 20 transfer loads associated with the support arm to the corresponding balance arm, while maintaining the level positioning of the lift platform 28. Thus, each support assembly 20 acts as a load transfer device, whereby in the event of a failure of one of the load bearing support arm pins, the load associated with the support arm is transferred to the
20 balance arm by one or more of the support assemblies.

Referring now to FIGURES 4 and 5, a support assembly 120 formed in accordance with another embodiment of the present invention will now be described in greater detail. The support assembly 120 of the second embodiment is identical in materials and operation to the first embodiment described above with the following
25 exception. The support assembly 120 includes a U-shape saddle strap 140 formed from a high strength material, such as steel. The saddle strap 140 extends from one side of the support arm 30a to the other side of the support arm 30a to cradle the balance arm 32a within the saddle strap 140. The saddle strap 140 is fastened to the support arm 30a by a plurality of fasteners 142, such as bolts, extending through
30 opposite sides of the saddle strap 140 and the support arm 30a.

5 In operation, in the event that the support arm pin 42 fails, the load of the support arm 30a is transferred to the balance arm 32a by the saddle strap 140. In the event support arm pin 42 fails, the support arm 30a or 30b is held in position by the torque tube 27. Because the saddle strap 140 is fastened to the support arm 30a, the saddle strap 140 is also held in position. However, because of the failed support arm pin 42, the lift platform 28 drops slightly until the balance arm 32a is received within the saddle strap 140. As a result, load is transferred to the balance arm 32a.

10 Referring now to FIGURES 6 and 7, a support assembly 220 formed in accordance with yet another embodiment of the present invention will now be described in greater detail. The support assembly 220 is identical in materials and operation to the embodiments described above with the following exceptions. As seen best by referring to FIGURE 6, the support assembly 220 includes a U-shaped retaining plate 222 extending between the support arm pin 42 and balance arm pin 44. Although the retaining plate 222 is suitably U-shaped in configuration, other
15 shapes, such as two plates pinned to the outboard and inboard facing sides of the support arm 30a and balance arm 32a, are also within the scope of the present invention.

As seen best by referring to FIGURE 7, the support arm pin 42 and balance arm pin 44 are seated within the support arm 30a and balance arm 32a, respectively,
20 on bushing housings 224a and 224b. The retaining plate 222 extends around one end of the support arm 30a and balance arm 32a and is coupled to each arm by the pins 42 and 44.

During normal operation, the support arm 30a and balance arm 32a are attached to the lift platform 28 using the support arm pin 42 and balance arm pin 44.
25 The support arm pin 42 and balance arm pin 44 are held in place by retaining rings (not shown) located on both ends. In the event of a pin breakage or displacement, the retaining plate 222 holds one of either the support arm 30a or balance arm 32a in place. The outer surface of the bushing housing 224a or 224b is trapped in place by the inner surface of shaft housing 226a or 226b, thereby constraining the system in
30 the event of a pin failure. Thus, the contact between the inner surface of the shaft

5

10

1968	1967	1966	1965	1964	1963	1962	1961	1960	1959	1958	1957	1956	1955	1954	1953	1952	1951	1950	1949	1948	1947	1946	1945	1944	1943	1942	1941	1940	1939	1938	1937	1936	1935	1934	1933	1932	1931	1930	1929	1928	1927	1926	1925	1924	1923	1922	1921	1920	1919	1918	1917	1916	1915	1914	1913	1912	1911	1910	1909	1908	1907	1906	1905	1904	1903	1902	1901	1900	1899	1898	1897	1896	1895	1894	1893	1892	1891	1890	1889	1888	1887	1886	1885	1884	1883	1882	1881	1880	1879	1878	1877	1876	1875	1874	1873	1872	1871	1870	1869	1868	1867	1866	1865	1864	1863	1862	1861	1860	1859	1858	1857	1856	1855	1854	1853	1852	1851	1850	1849	1848	1847	1846	1845	1844	1843	1842	1841	1840	1839	1838	1837	1836	1835	1834	1833	1832	1831	1830	1829	1828	1827	1826	1825	1824	1823	1822	1821	1820	1819	1818	1817	1816	1815	1814	1813	1812	1811	1810	1809	1808	1807	1806	1805	1804	1803	1802	1801	1800	1799	1798	1797	1796	1795	1794	1793	1792	1791	1790	1789	1788	1787	1786	1785	1784	1783	1782	1781	1780	1779	1778	1777	1776	1775	1774	1773	1772	1771	1770	1769	1768	1767	1766	1765	1764	1763	1762	1761	1760	1759	1758	1757	1756	1755	1754	1753	1752	1751	1750	1749	1748	1747	1746	1745	1744	1743	1742	1741	1740	1739	1738	1737	1736	1735	1734	1733	1732	1731	1730	1729	1728	1727	1726	1725	1724	1723	1722	1721	1720	1719	1718	1717	1716	1715	1714	1713	1712	1711	1710	1709	1708	1707	1706	1705	1704	1703	1702	1701	1700	1699	1698	1697	1696	1695	1694	1693	1692	1691	1690	1689	1688	1687	1686	1685	1684	1683	1682	1681	1680	1679	1678	1677	1676	1675	1674	1673	1672	1671	1670	1669	1668	1667	1666	1665	1664	1663	1662	1661	1660	1659	1658	1657	1656	1655	1654	1653	1652	1651	1650	1649	1648	1647	1646	1645	1644	1643	1642	1641	1640	1639	1638	1637	1636	1635	1634	1633	1632	1631	1630	1629	1628	1627	1626	1625	1624	1623	1622	1621	1620	1619	1618	1617	1616	1615	1614	1613	1612	1611	1610	1609	1608	1607	1606	1605	1604	1603	1602	1601	1600	1599	1598	1597	1596	1595	1594	1593	1592	1591	1590	1589	1588	1587	1586	1585	1584	1583	1582	1581	1580	1579	1578	1577	1576	1575	1574	1573	1572	1571	1570	1569	1568	1567	1566	1565	1564	1563	1562	1561	1560	1559	1558	1557	1556	1555	1554	1553	1552	1551	1550	1549	1548	1547	1546	1545	1544	1543	1542	1541	1540	1539	1538	1537	1536	1535	1534	1533	1532	1531	1530	1529	1528	1527	1526	1525	1524	1523	1522	1521	1520	1519	1518	1517	1516	1515
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------